

BIOGAS DEHUMIDIFICATION SYSTEM

HRS BDS SERIES



The HRS BDS Series is an efficient solution to cool and dehumidify biogas for combustion with two standard options. The system condenses up to 90% of the water contained in the gas, which is continuously separated before the lean biogas is ready for use. This is a necessary process for all bio-energy plants that use biogas as fuel in CHP engines.

A heat recovery step can be included as a standard option thus reducing energy costs up to 20%. Cold gas at 5°C is used to precool the incoming gas at 40°C, whilst raising the temperature of the dehumidified gas to approximately 36°C before use. A chiller is included to provide the energy required for the process.

The BDS comes complete with controls in a packaged 'plug and play' skid.

TECHNICAL DATA

APPLICATIONS

Biogas Dehumidification
Biogas Cooling

SURFACE FINISH

External: Matt
Internal: Matt

STANDARD MATERIALS OF CONSTRUCTION

Service Side: AISI 304 Stainless Steel
Biogas Side: AISI 316L Stainless Steel
Other material options available

STANDARD DESIGN CONDITIONS

Service Side: 6 bar/80°C
Biogas Side: 2 bar/80°C

STANDARD CONNECTIONS

Service Side: Flange
Product Side: Flange
All flange types available

FEATURES

- Condenses >90% of the water present in biogas
- Up to 20% energy recovery available, reducing energy costs
- Skid-mounted for easy access and freedom of movement
- Automatic control panel
- ATEX-compliant version available
- Unit insulated with Armaflex

RANGE

| MODELS | GAS FLOW (kg/hr) | T GAS IN (°C) | T GAS MIN (°C) | T GAS OUT (°C) | T SERVICE IN (°C) | T SERVICE OUT (°C) | THERMAL DUTY CHILLER (kW) | ELECTRICITY CONS. (kW) |
|---------|------------------|---------------|----------------|----------------|-------------------|--------------------|---------------------------|------------------------|
| BDS 13 | 161 - 200 | 40 | 7 | 31 | 0.5 | 5.5 | 10.8 | 4.5 |
| BDS 21 | 200 - 350 | 40 | 7 | 32 | 0.5 | 5.5 | 15.3 | 6.6 |
| BDS 37 | 350 - 540 | 40 | 7 | 34 | 0.5 | 5.5 | 26.1 | 11.4 |
| BDS 55 | 540 - 700 | 40 | 7 | 34 | 0.5 | 5.5 | 30.2 | 12.6 |
| BDS 73 | 700 - 1050 | 40 | 7 | 36 | 0.5 | 5.5 | 45 | 20.7 |
| BDS 121 | 1050 - 1700 | 40 | 7 | 36 | 0.5 | 5.5 | 72.5 | 30.4 |


DESIGN CODE AND COMPLIANCE

PD 5500, PED 2014/68/EU, ASME | TR CU 032, DOSH Compliant

BIOGAS DEHUMIDIFICATION SYSTEM

HRS BDS SERIES

STANDARD OPTION



HEAT RECOVERY OPTION

