

INDUSTRIAL DOUBLE TUBE HEAT EXCHANGERS WITH REMOVABLE TUBE



The HRS DTIR Series is a complete stainless steel double tube heat exchanger designed for industrial and environmental applications. The product flows through the inner tubes and the service fluid flows through the surrounding shell. As a result of its geometry, the DTIR Series has a continuous freepass cross section allowing large particles to be processed and reduces the risk of product blockages.



The removable inner tube allows for effective cleaning of both shell and tube, making it ideal for product to product applications. Using our corrugation technology, heat transfer and efficiency are increased over standard smooth and dimple tube heat exchangers. In addition, potential fouling is minimised.

TECHNICAL DATA_

Sludge Heating/Cooling & Pasteurisation Digester Heating Sludge-to-Sludge Heat Recovery

Service Side:AISI 316L Stainless SteelProduct Side:AISI 316L Stainless SteelOther material options available

Service Side: Flange Product Side: Flange All flange types available External: Internal:

Matt Matt

Service Side: Product Side: 10 bar/185°C 10 bar/185°C

Corrugated tubes for increased heat transfer

Multiple units can be interconnected and have the option of frame mounting, insulation and cladding in stainless steel

| MODELS | LENGTHS (m) | SURFACE AREA (m²) | SERVICE SIDE CONNECTION | PRODUCT SIDE CONNECTION | MAX FLOW SERVICE (m ³ /hr) | MAX FLOW PRODUCT (m ³ /hr) | SERVICE SIDE VOLUME (I) | PRODUCT SIDE VOLUME (I) |
|---------------|----------------|----------------------|-------------------------|-------------------------|--|--|----------------------------|----------------------------|
| DTIR 51/25 | 3 - 6 | 0.4 | DN40 | DNI5 | 13 | 4 | 8.2 | 2.5 |
| DTIR 64/38 | 3 - 6 | 0.6 | DN40 | DN25 | 17 | 10 | 10.3 | 5.7 |
| DTIR 76/51 | 3 - 6 | 0.9 | DN40 | DN40 | 18 | 18 | 14.1 | П |
| DTIR 104/64 | 3 - 6 | 1.1 | DN65 | DN50 | 43 | 29 | 29.7 | 16.9 |
| DTIR 104/76 | 3 - 6 | 1.3 | DN65 | DN65 | 33 | 41 | 21.5 | 24.8 |
| DTIR 129/104 | 3 - 6 | 1.8 | DN80 | DN80 | 37 | 77 | 26 | 46.4 |
| DTIR 168/129* | 3 - 6 | 2.4 | DN100 | DN100 | 55 | 120 | 45.4 | 73.6 |

The surface area and volumes shown are for 6m length models. *DTIR 168/129: the pressure for this unit cannot be more than 5 bars.

PD 5500, PED 2014/68/EU, ASME | TR CU 032, DOSH Compliant

HRS HEAT EXCHANGERS hrs-heatexchangers.com Australian Office +61 3 9489 1866 New Zealand Office +64 9 889 6045 info@anz.hrs-he.com