



## INDUSTRIAL DOUBLE TUBE HEAT EXCHANGERS WITH REMOVABLE TUBE



The HRS DTIR Series is a complete stainless steel double tube heat exchanger designed for industrial and environmental applications. The product flows through the inner tubes and the service fluid flows through the surrounding shell. As a result of its geometry, the DTIR Series has a continuous free-pass cross section allowing large particles to be processed and reduces the risk of product blockages.



The removable inner tube allows for effective cleaning of both shell and tube, making it ideal for product to product applications. Using our corrugation technology, heat transfer and efficiency are increased over standard smooth tube heat exchangers. In addition, potential fouling is minimised.

### TECHNICAL DATA

Sludge Heating/Cooling & Pasteurisation  
 Digester Heating  
 Sludge-to-Sludge Heat Recovery

External: Matt  
 Internal: Matt

Service Side: AISI 316L Stainless Steel  
 Product Side: AISI 316L Stainless Steel  
 Other material options available

Service Side: 10 bar/185°C  
 Product Side: 10 bar/185°C

Service Side: Flange  
 Product Side: Flange  
 All flange types available

- Corrugated tubes for increased heat transfer
- Multiple units can be interconnected and have the option of frame mounting, insulation and cladding in stainless steel

MODELS	LENGTHS (m)	SURFACE AREA (m <sup>2</sup> )	SERVICE SIDE CONNECTION	PRODUCT SIDE CONNECTION	MAX FLOW SERVICE (m <sup>3</sup> /hr)	MAX FLOW PRODUCT (m <sup>3</sup> /hr)	SERVICE SIDE VOLUME (l)	PRODUCT SIDE VOLUME (l)
DTIR 51/25	3 - 6	0.4	DN40	DN15	13	4	8.2	2.5
DTIR 64/38	3 - 6	0.6	DN40	DN25	17	10	10.3	5.7
DTIR 76/51	3 - 6	0.9	DN40	DN40	18	18	14.1	11
DTIR 104/64	3 - 6	1.1	DN65	DN50	43	29	29.7	16.9
DTIR 104/76	3 - 6	1.3	DN65	DN65	33	41	21.5	24.8
DTIR 129/104	3 - 6	1.8	DN80	DN80	37	77	26	46.4
DTIR 168/129*	3 - 6	2.4	DN100	DN100	55	120	45.4	73.6

The surface area and volumes shown are for 6m length models. \*DTIR 168/129: the pressure for this unit cannot be more than 5 bars.

PD 5500, PED 2014/68/EU, ASME | TR CU 032, DOSH Compliant

**HRS HEAT EXCHANGERS** | [hrs-heatexchangers.com](http://hrs-heatexchangers.com) | **Malaysian Office** | +603 8081 1898 | [info@my.hrs-he.com](mailto:info@my.hrs-he.com)