


## INDUSTRIAL DOUBLE TUBE HEAT EXCHANGERS WITH REMOVABLE TUBE

### HRS DTIR SERIES



The HRS DTIR Series is a complete stainless steel double tube heat exchanger designed for industrial and environmental applications. The product flows through the inner tubes and the service fluid flows through the surrounding shell. As a result of its geometry, the DTIR Series has a continuous free-pass cross section allowing large particles to be processed and reduces the risk of product blockages.

The removable inner tube allows for effective cleaning of both shell and tube, making it ideal for product to product applications. Using our corrugation technology, heat transfer and efficiency are increased over standard smooth tube heat exchangers. In addition, potential fouling is minimized.



## TECHNICAL DATA

### APPLICATIONS

Sludge Heating/Cooling & Pasteurization  
Digester Heating  
Sludge-to-Sludge Heat Recovery

### SURFACE FINISH

External: Matt  
Internal: Matt

### STANDARD MATERIALS OF CONSTRUCTION

Service Side: AISI 316L Stainless Steel  
Product Side: AISI 316L Stainless Steel  
*Other material options available*

### STANDARD DESIGN CONDITIONS

Service Side: 147 PSI/365°F  
Product Side: 147 PSI/365°F

### STANDARD CONNECTIONS

Service Side: Flange  
Product Side: Flange  
*All flange types available*

### FEATURES

- Corrugated tubes for increased heat transfer
- Multiple units can be interconnected and have the option of frame mounting, insulation and cladding in stainless steel

### RANGE

MODELS	LENGTHS (ft)	SURFACE AREA (ft <sup>2</sup> )	SERVICE SIDE CONNECTION	PRODUCT SIDE CONNECTION	MAX FLOW SERVICE (gpm)	MAX FLOW PRODUCT (gpm)	SERVICE SIDE VOLUME (gal)	PRODUCT SIDE VOLUME (gal)
DTIR 51/25	10 - 20	4	1.5"	0.5"	57	18	2	1
DTIR 64/38	10 - 20	7	1.5"	1"	75	44	3	2
DTIR 76/51	10 - 20	10	1.5"	1.5"	79	79	4	3
DTIR 104/64	10 - 20	12	2.5"	2"	189	128	8	4
DTIR 104/76	10 - 20	14	2.5"	2.5"	145	181	6	7
DTIR 129/104	10 - 20	19	3"	3"	163	339	7	12
DTIR 168/129*	10 - 20	26	4"	4"	242	528	12	19

The surface area and volumes shown are for 20ft length models. \*DTIR 168/129: the pressure for this unit cannot be more than 72.5 PSI.

### DESIGN CODE AND COMPLIANCE

PD 5500, PED 2014/68/EU, ASME | TR CU 032, DOSH Compliant